

NOTES:

- 1. THIS IS A ULTRA-HIGH VACUUM COMPONENT (UHV).
- 2. WHEN MACHINING VACUUM PARTS, USE OF SILICONE AND SULPHUR-BASED CUTTING FLUIDS IS PROHIBITED. USE ONE OF THE FOLLOWING:
 - A) CIMCOOL 5 STAR 49
 - B) TRIM SOL
- 3. KEEP THE PART CLEAN AND WRAP FOR UHV PACKING WITH ALUMINUM FOIL.
- 4. ALL DIMENSIONS IN [] ARE MILLIMETERS AND ARE FOR REFERENCE ONLY.

	ITEM DWG/PART NUMBER	NOMENCLATURE OR DESCRIPTION	N MATERIAL / SPEC QTY
	PARTS LIST		
	ALL DIMENSIONS ARE IN INCHES TOLERANCES DECIMALS ANGULAR	A2455100 ARG	THIS DRAWING IS THE PROPERTY OF GONNE NATIONAL LABORATORY
	XXX = .01 XXX = .005 SURFACE ROUGHNESS 63 REMOVE ALL BURRS AND	DATE CHIEF DESIGN ENGINEER R. KRAKORA 5/3/96 D.SHU CHECKED BY DATE GP LEADER J.CHANG 6/18/96 T.M.KUZAY DESIGNER DATE PROJECT MGR	6/24/96 ADVANCED PHOTON SOURCE 6/26/96 Y3-30 MIRROR MOUNT ASSEMBLY FOR SRICAT
	SURFACE TEXTURE TO BE IN ACCORDANCE WITH LATEST ANSI B46.1	KRAKORA/CHAN(\$5/3/96 RESPONSIBLE ENGINEER DATE APPROVED/RELEASED J.CHANG 6/18/96	2-BM-A 1200mm MIRROR TIE ROD
SYM CHANGE DESCRIPTION BY CHKD DATE REVISIONS		STAINLESS STEEL TYPE 303	1:1 SHEET 1.3+ B P4105091203-340004-00